

Layer Fizic

Standard	IEEE 802.16e-2005 (WiMAX) Wave 2
Tip antena	Antena Omni Integrata (2dBi)
Frecventa	3.3GHz - 3.6GHz
Modulare adaptiva	DL: QPSK, 16QAM, 64QAM
	UL: QPSK, 16QAM, 64QAM
Latimea canalului	5 , 7, 10MHz

Mi-Fi:

- Permite utilizarea aceleiasi conexiuni pentru mai multe echipamente de acces sau mai multi utilizatori
- Disponibil oriunde, acasa sau in miscare

Networking

Compatibilitate sisteme de operare	Wi-Fi: NA; USB: Windows/ Mac OSX /Linux
Suporta	DNS, NAT, DHCP, VPN, Firewall
Protocoale de configurare si management la distanta	SNMP v2c, TR069, OMA-DM
Management local	Acces web browser, CLI, Telnet
Mentenanata software	OTA (Over-the-air) software upgrade

Interfete

USB	1 USB 2.0
WiFi AP	802.11b/g

Electrica si Mecanica

Dimensiuni (lungime x latime x grosime)	14.8mm x 96mm x 50mm
Greutate	62g
Temperatura de functionare	0°C - 50°C
MTBF	50,000 ore
Sursa alimentare	USB
Battery	Li-Polymer (1800mAh); Operational: 4 ore. Standby: 18 ore. Hibernare: 9 zile

RETEAUA TA PERSONALA Wi-Fi



DISPONIBIL ORIUNDE

1

